

DS-K1T801 Series

Time & Attendance and Access Control Terminal

AVAILABLE MODELS

- DS-K1T801E (EM Card Only)
- DS-K1T801M (M1 Card Only)



MAIN FEATURES

- 32-bit processor
- Stand-alone operation management settings
- Max. 3000 card number settings
- Supports authentication method of card and card & password
- Supports exit button
- Supports ID card, and ID card number reading (DS-K1T801E)
- Supports Mifare card, Mifare card number reading (DS-K1T801M)
- Watchdog design
- Data can be permanently saved after power-off

SPECIFICATIONS

Model	DS-K1T801E	DS-K1T801M
Parameters		
Processor	32bit	
Storage	Storage for 3000 Legal Card Information	
Card type	EM Card	Mifare Card
Input interface	Exit Button × 1, Door Sensor × 1	
Output interface	Doorbell × 1, E-lock Output × 1	
Key board	13 Keys (0-9, *, #, Doorbell)	
LED Indicator	Power/Status	

Model	DS-K1T801E	DS-K1T801M
Parameters		
Voice prompt	Beeper	
Working voltage	12V DC	
Working current	0.17A (without Load)	
Working Temperature	-20°C to 65°C (-4° F to 149° F)	
Working Humidity	10% to 90% (No Condensing)	
Dimension	126.5(L)mm × 94.5(W)mm × 24(H)mm (4.98" × 3.72" × 0.94")	