

QT302RXR

Quantec Master Infrared Ceiling Receiver (Round Version)



Overview

An unobtrusive white round version of our Quantec Master Ceiling Receiver.

Designed to accept infrared calls from compatible Quantec staff attack transmitters, patient neck/wrist pendants and staff attendance pendants.

Typically used in bedrooms, corridors, common rooms and any other area requiring infrared coverage.

Include a red confidence light.

Typical 10m line of sight receiving range.

Up to three QT302RXRS slave receivers can be connected to a master ceiling receiver to increase IR coverage.

OptionalQT848/10 locking kit, complete with 10 grubscrews and Allen key, also available.

Technical Specifications

T 01942 322744

Power requirements	TBC.
Quiescent current	TBC.
Indicators	Red/green confidence LED/diffuser.

LPCB 💆

ISCE The Restruce of Sound and 

F 01942 829867 **W** www.c-tec.com



E sales@c-tec.co.uk



Controls	n/a.
Connections	N+: N-; R; G; L+; IR
Expansion connections	R; G; IR; N+ and N- terminals allow the connection of optional slave overdoor lights and slave infrared receivers.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Sounder	No.
Onboard Infrared Receiver	Yes - will accept calls from compatible Quantec infrared transmitters.
Product dimensions (mm)	81mm diameter x 27mm deep. Designed for ceiling mounting only. Base fits 16mm conduit and BESA centres.
Construction & finish	White round plastic.
IP Rating	TBC.
Weight	42g
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.
Notes	Optional QT848/10 locking kit, complete with 10 grubscrews and Allen key, available.



T 01942 322744 E sales@c-tec.co.uk **F** 01942 829867

W www.c-tec.com

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom







T 01942 322744 E sales@c-tec.co.uk **F** 01942 829867 W www.c-tec.com

