

QT606S

Slave Overdoor Light c/w Sounder



Overview

Provides audible and visual indication of calls made from a Quantec call point outside bedrooms, WCs, etc.

Flash and sound rates change/intensify to reflect the urgency of the incoming call.

Dual red and green LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Finished in tough, durable ABS plastic.

Also available as part of the QT951 Accessible Toilet Alarm kit.

Technical Specifications

Quiescent current	Less than 1.5mA.
Alarm current	40mA.
Indicators	Dual ultra-bright red and green Alarm LEDs (Flash rate and colour sequence changes/intensifies to reflect the urgency of the incoming call).



Connections	R (Red); G (Green); Net +; Net -. Wire as a slave to a Quantec Addressable Call Point or Accessible Toilet Reset Point. See instructions for details.
Onboard Sounder	Yes. (Sound sequence changes and intensifies to reflect the urgency of the incoming call).
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 54 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	58g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom