

# DMO-700 CONTROL PANEL

The DMO-700 control panel is used to immediately start the digitexCZK/IP® system on the premises where it operates. The control panel is designed to control alarm sirens, both locally and remotely. The DMO-700 control panel is adapted to the customer's needs and, depending on the preferences, it can support up to 12 alarm buttons.

## ADVANTAGES AND FEATURES

### ACTIVATION OF ELECTRONIC SIRENS

DMO-700 enables immediate activation of a siren or group of sirens. Via the control panel, the dispatcher can deliver a message, activate an alarm or activate alarm with the announcement.

### REMOTE CONTROL

In addition to the local control of electronic sirens, you can activate sirens remotely via radio transmission or LAN using digitexCZK/IP® software.

### INTUITIVE OPERATION

Local activation of sirens is carried out by pressing a button on the control panel enclosure or using a microphone for transmitting live voice messages via electronic sirens assigned to the control panel.

### PERMANENT OPERATION

The control panel provides uninterrupted access to electronic siren management, even in the event of 230VAC mains power failure. The device automatically switches to the back-up power supply mode (from the built-in battery) guaranteeing its reliability.

### FORWARDING MESSAGES

Announcement of any alarm or warning messages (live and with any content) takes place via a microphone installed in the control panel.

### SIREN TEST

The control panel has a TEST function that allows you to run a siren or a group of sirens assigned to the device in order to perform their full troubleshooting.



## TECHNICAL DATA

<b>Local control</b>	up to 12 alarm buttons 1 siren test button 1 handheld microphone
<b>Remote control</b>	LAN (with digitexCZK/IP®) RF transmission
<b>Control of DSE electronic sirens</b>	1 group of sirens via LAN in the digitexCZK/IP® system
<b>Control of electromechanical sirens</b>	option
<b>Power supply</b>	230VAC (50-60Hz) back-up supply (7-26Ah)
<b>Material, degree of protection</b>	Lockable metal enclosure, IP66
<b>Dimensions</b>	380 (H) × 380 (W) × 210 (D) mm (w/o microphone)
<b>Weight</b>	14 kg (without batteries)
<b>Warranty</b>	24 months (battery: 12 months)

