

DMS-18B LOCAL CONTROL PANEL

The DMS-18B control panel is used for local operation of the electronic siren. It enables the dispatcher to quickly manage the electronic siren via a keyboard to operate the siren function and an additional microphone connected.

ADVANTAGES AND FEATURES

TURNING ON THE SIREN

The control panel has the ALARM function, which is used to immediately start the siren.

SIREN TEST

The control panel has a TEST function that allows you to run the siren test function.

RUNNING MACROS

DMS-18B allows to run 8 different alarms stored in the siren memory (pre-programmed) in the GSE-24 or PC-550 module (depending on the DSE siren configuration).

CONTINUOUS SIREN OPERATION

DMS-18B panel control are powered by an electronic siren. In the event of a 230V power supply failure, the panel still works allows to the siren batteries.

FORWARDING MESSAGES

The desk microphone connected to the control panel (Jack socket) allows the dispatcher can transmit any voice messages via the electronic siren.

EXTERNAL SOURCE AUDIO

The DMS-18B allows to connect an external audio source, eg. a wave file from a computer (Jack socket).



TECHNICAL PARAMETERS

Power supply	24 V DC
Power consumption in stand by	6 mA
Power consumption at work	12 mA
Communication with DSE	4 pair shielded cable (max. 50 m) FTP is suitable
Truck audio	Jack socket
Material	plastic ABS
Dimensions	32 h. x 125 l. x 150 d. mm
Weight	350 g
Warranty	24 months

